Appln. No.: 10/812,878

## IN THE CLAIMS:

Please cancel Claim 24 without prejudice or disclaimer of the subject matter recited therein.

Please amend Claims 3 and 23 as follows.

Claims 1 and 2. (Cancelled).

3. (Currently Amended) A manipulator comprising:

first and second contact portions opposing each other and facing a

manipulation target object;

first openings at said first contact portion,

second openings at said second contact portion, and

fluid control means for performing an operation of feeding the manipulation

target object by ejecting a first fluid at a first flow velocity from each of at least one of the first

and second openings at a front side of the manipulation target object in a feeding direction and

ejecting a second fluid at a second flow velocity slower than the first flow velocity from at least

one of the first and second openings at a rear side of the manipulation target object in the feeding

direction and at least one of the second openings behind the target object so that the ejected fluids

collide to generate a flow which pushes the manipulation target object in a forward direction.

Claims 4-22. (Cancelled).

Appln. No.: 10/812,878

## 23. (Currently Amended) A manipulator comprising:

first and second contact portions opposing each other and facing a manipulation target object:

first openings at said first contact portion,

second openings at said second contact portion, and

fluid control means for controlling an attitude of the manipulation target object by ejecting a fluid from at least one of the first openings and drawing a fluid from at least one of the second openings at a right side of a center of gravity of the manipulation target object and ejecting a fluid from at least one of the second openings and drawing a fluid from at least one of the first openings at a left side of the center of gravity of the manipulation target object so as to generate a couple force around the center of gravity of the manipulation target object.

Claim 24. (Cancelled).